

USA



INVESTOR IN PEOPLE



**CERTIFIED COPY OF  
PRIORITY DOCUMENT**



The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., L.C. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

*[Signature]*


Dated 3 October 2000



#72131  
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Ahmed Karmouch; Tom Gray; Serge Mankovskii; Cui Zheng  
Serial No.: 09/676,838 Art Unit: Unknown  
Filed: September 29, 2000  
Title: SECURITY MECHANISMS AND ARCHITECTURE FOR COLLABORATIVE  
SYSTEMS USING TUPLE SPACE  
Examiner: Unknown  
Docket No.: 481340010027



RECEIVED  
DEC 08 2000  
Technology Center 2100

Commissioner for Patents  
Washington, D.C. 20231

Sir:

We now enclose a certified copy of United Kingdom Application Serial No. 9923544.2 filed on October 5, 1999 by Mitel Corporation and The University of Ottawa, assignees of Ahmed Karmouch, Tom Gray, Serge Mankovskii, and Cui Zheng for "Security Mechanisms And Architecture For Collaborative Systems Using Tuple Space."

Convention priority is claimed on the basis of this application.

Respectfully submitted,

JONES, DAY, REAVIS & POGUE

By:

David B. Cochran

David B. Cochran, Reg. No. 39,142

North Point  
901 Lakeside Avenue  
Cleveland, Ohio 44114  
(216) 586-3939

Attorney for Applicant

I hereby certify that this correspondence is being deposited today with the United States Postal Service as first class mail in an envelope addressed to: Commissioner for Patents, Washington, D.C. 20231  
on 11/29/2000

By: Deborah A. Sateran



The  
Patent  
Office

1/77

7/77

9/77 - £130 + £15

08/09 E481854-6 D02094

P01/7700 0.00 - 9923544.2

Request for grant of a patent

5 OCT 1999

1/77

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1.	Your reference	03 34676		
2.	Patent application number	9923544.2		- 5 OCT 1999
3.	Full name, address and post code of the or each applicant	Mitel Corporation and The University of Ottawa 350 Legget Drive 550 Cumberland PO Box 13089 Room 160 Kanata, Ontario Ottawa, Ontario K2K 1X3 Canada K1N 6N5 Canada		
	Patents ADP number	607671002 7697972001		
	If the applicant is a corporate body, give the country/state of its incorporation	CA		
4.	Title of the invention	Security Mechanisms And Architecture For Collaborative Systems Using Tuple Space		
5.	Name of your agent	VENNER, SHIPLEY & CO		
	"Address for service" in the United Kingdom to which all correspondence should be sent	20 LITTLE BRITAIN LONDON EC1A 7DH		
	Patents ADP	1669004		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and the or each application number	Country	Priority application number	Date of filing
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and filing date of the earlier application	Number of earlier application	Date of Filing	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request?	Yes		

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	19
Claim(s)	3
Abstract	1
Drawing(s)	6

10. If you are also filing any of the following state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) one

Request for preliminary examination and search (*Patents Form 9/77*) one

Request for substantive examination (*Patents Form 10/77*)

Any other documents

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

5 October 1999

*Werner, Shupley & Co*

12. Name and daytime telephone number of person to contact in the United Kingdom

MATTHEW READ  
0171-600 4212

Patents Form 7/77

Patents Act 1977  
(Rule 15)

The  
Patent  
Office

5 OCT 1999

7/77

Statement of inventorship and  
of right to grant of a patent

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference 03 34676

2. Patent application number **9923544.2**

**5 OCT 1999**

3. Full name, address and post code of the or  
each applicant

Mitel Corporation and The University of Ottawa	
350 Legget Drive	550 Cumberland
PO Box 13089	Room 160
Kanata, Ontario	Ottawa, Ontario
K2K 1X3 Canada	K1N 6N5 Canada

Patents ADP number

If the applicant is a corporate body, give the  
country/state of its incorporation

CA

4. Title of the invention

Security Mechanisms And Architecture For Collaborative  
Systems Using Tuple Space

5. State how the applicant(s) derived the right  
from the inventor(s) to be granted a patent

By virtue of the inventors employment by the Applicants

6. How many, if any, additional Patents Forms  
7/77 are attached to this form?

7.

I/We believe that the persons named over the page (and on any extra  
copies of this form) is/are the inventor(s) of the invention which the  
above patent application relates to.

Signature

Date

5 October 1999

8. Name and daytime telephone number of  
person to contact in the United Kingdom

*Matthew Read*  
MATTHEW READ  
0171-600 4212

**Patents Form 7/77**

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Ahmed KARMOUCH  
2000 Rolling Brook Drive  
Gloucester, Ontario  
K1W 1C7 Canada

Patents ADP number 7755028001

Tom GRAY  
11 Pineridge Road  
RR3 Carp, Ontario  
K0A 1L0 Canada

Patents ADP number 7249469001

Serge MANKOVSKII  
3096 Old Almonte Road  
Carp, Ontario  
K0A 1L0 Canada

Patents ADP number 7280613001



Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Cui <u>ZHENG</u> <del>206 Mann Avenue</del> <del>Ottawa, Ontario</del> <del>K1N 6Y7 Canada</del>	c/o Sim & McBurney 6 <sup>th</sup> Floor 330 University Ave. Toronto Canada M5G 1R7
Patents ADP number	7755010001

AIL  
24.129

7755010002

Patents ADP number

Patents ADP number

**THIS PAGE BLANK (USPTO)**

# SECURITY MECHANISM AND ARCHITECTURE FOR COLLABORATIVE SOFTWARE SYSTEMS USING TUPLE SPACE

## FIELD OF THE INVENTION

5

This invention relates in general to mobile communications systems, and more particularly to a method of effecting secure mobile communications by means of user authentication, user authorization and communication privacy.

## 10 BACKGROUND OF THE INVENTION

One emerging and attractive paradigm in network communications is Mobile Computing, which combines traditional data networks and telecommunication networks in a mobile computing environment. Communication may be provided, not  
15 only between fixed and/or mobile devices, but also in accordance with personalized services and resources which are accessible to a mobile users at any time and place (see, for example, A. Hooda, A. Karmouch, S. Abu-Hakima, "Nomadic Support Using Agents", 4<sup>th</sup> *International Symposium on Internetworking*, Ottawa, July 1998).

20 The increased flexibility afforded by mobile computing has come at the expense of eroded network security. When a user roams the network and remotely accesses services and/or resources on the network, network integrity can be exposed to significant security risks. Specifically, various types of attack can be launched at any enabled access location on the network. Passive wiretapping, active wiretapping,  
25 IP sniffing, and identity spoofing are only some examples of these types of attacks.

## SUMMARY OF THE INVENTION

30 According to the present invention, a secure agent communications system is provided for operation in conjunction with a Blackboard Messaging System (BMS) such as MicMac. An overall framework is developed for a general case of multi-agent communication to mutually authenticate parties and establish secure dynamic sessions. This framework is implementation independent and capable of supporting

different authentication and key exchange protocols. Moreover, the system according to the present invention accommodates both the protection of pure communication data and information used for control purposes (e.g. routing, QoS, etc.)

5           Therefore, in accordance with an aspect of the invention there is provided a virtual network communication system for effecting secure communications between user agents at different sites within said virtual network, comprising at least one Private Tuple Space within each of the sites for effecting intra-site communications between the agents, a Shared Tuple Space for effecting inter-site communications  
10 between different sites, and a Coordinator Manager within each of the sites for receiving user initiated communication requests from the Private Tuple Space to communicate between user agents at the different sites, authenticating the requests and in response dynamically creating and managing instances of Coordinators at each of the different sites which embed messages from the user agents in secure tuples and  
15 exchange the secure tuples over the Shared Tuple Space.

          According to another aspect of the invention there is provided a method of effecting secure virtual network communications between user agents at different sites within said virtual network, comprising the steps of authenticating user initiated  
20 requests to communicate between user agents at different sites, generating and forwarding an inner key to each of the user agents at the different sites for encrypting and decrypting messages exchanged there between, and dynamically creating and managing instances of Coordinators at each of the different sites for embedding the messages in secure tuples and exchanging the secure tuples over a Shared Tuple Space  
25 between the different sites.

          In accordance with yet another aspect of the invention, the method includes steps of generating two dynamic identifiers for creating the Coordinator instances and generating a hashed value of the inner key for encrypting and decrypting the secure  
30 tuples.

## BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of a preferred embodiment of the present invention is provided herein below with reference to the following drawings, in which:

5

Figure 1A is a three-layered architecture diagram of a Personal Mobility Management System (PMMS) forming the preferred environment for implementation of the present invention;

10

Figure 1B is a schematic illustration of inter-site communication using a shared Agora for the PMMS system of Figure 1A;

Figure 2 is a block diagram of a secure communication framework in accordance with the present invention;

15

Figure 3 is a message flow diagram showing a sequence of messages for an exemplary communication session in accordance with the principles of the present invention;

20

Figure 4 is a block diagram of the secure communication framework of Figure 2 for the exemplary communication session of Figure 3; and

Figure 5 shows a preferred format for an inter-site communication tuple format in accordance with the present invention.

25

Figure 6 is the message flow diagram of Figure 3 expanded to show authentication and key exchange transactions in accordance with the preferred embodiment.

30

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the absence of explicit mechanisms, personal communication over an unsecure channel like the Internet can be viewed or modified, registered users can be

impersonated, users' accounts can be compromised, etc. As discussed in greater detail below, the security principles of the present invention have been applied to a prototype mobile computing system known as Personal Mobility Management System (PMMS). This system has been designed and implemented by the Mobile Agent Alliance, which is a collaboration of the University of Ottawa, Mitel Corporation and the National Research Council of Canada. PMMS provides personalized services and access to resources for nomadic users over a network, resulting in a mobile working environment which is similar to the user's home environment. PMMS implements dynamic mapping between a user and the shared devices (or services) available at any location within the network. The dynamic mapping functionality is obtained using the Internet *LDAP* directory. Another inherent aspect of PMMS is universal messaging for handling the communications needs of mobile users. Messaging is largely addressed by the interaction of autonomous programs (agents), representing users, services, and data resources.

Figure 1A shows the three-layered architecture of PMMS. Each enabled site within the virtual network maintains this or an analogous structure. Each site also manages a X.500 Directory Information Base (DIB) for its organizational network. This DIB physically resides in the first layer (i.e. in the Data Repository (referred to occasionally hereinafter as D.R.)). The first layer (Layer 1) contains all of the data information such as user profiles, service profiles and access policies. This layer is only accessible to the middle layer (Layer 2).

Layer 2 deploys intra-site processing agents, as follows:

- **Site Profile Agent** negotiates, with its remote peer (in a user's home site), the user's preferences, and dynamically determines the authorized services for the user, in accordance with the two sets of policies of both concerned sites.
- **Policy Server** maintains the obligations and authorizations allowed or denied to each agent. The server contains the private knowledge base (for each site) regarding authorized services, accessible resources and management rules (cost, delay, privileges, etc.).
- **Resource Agent** negotiates, with its peer, resources for each requested and authorized service. It also creates an environment for this service. Negotiation

between two resource agents determines the availability and accessibility of local resources before processing the service.

- **Coordinator** manages the inter-agent communications. Its central role is to establish communication among two or more agents (locally or remotely), to locate agents and to control their activities when exchanging information.

Layer 3 presents a Graphical User Interface (GUI) for the nomadic users. It contains agents and interfaces for user authentication and service access. A mobile user logs onto the system via the User Logon Agent, which functions as the authentication client of the system. After receiving user information as input by the user, the User Logon Agent locates the user in the virtual network and authenticates the user as the one he/she claims to be. A Service Access Agent is responsible for providing dynamically located services to the authenticated user. This interface will not be displayed if the user cannot be identified by his/her home site.

Interactions between agents are established through the exchange of KQML messages over the MicMac blackboard messaging system developed by Mitel Corporation (see *Feature Interaction Visualization and Resolution in an Agent Environment*, by Buhr et al in *Feature Interactions in Telecommunications and Software Systems V*, K. Kimbler, L.G. Bouma Eds, IOS Press, Amsterdam 1998). MicMac is a set of software tools, which provide an environment to support hands-on experimentation with multi-agent interaction and negotiation protocols. It allows for the creation and the manipulation of one or more Agoras (i.e. tuple spaces). A tuple space is an open area for exchanging information. An example of a shared tuple space is shown in Figure 1B for effecting inter-site communication according to the principles of the present invention. In this example, the tuple space is shared among three organizations, namely Mitel Corporation, National Research Council of Canada and University of Ottawa. Inter-organization communication messages are exchanged on this shared tuple space, while each organization may implement their own private tuple space in order to handle inter agent communications.

The server supports access by co-located clients as well as by remote (networked) clients. Network connections do not directly end up at the Agora server

itself; actually they are handled by a specialized local Agora client acting as a shared proxy for networked clients. The service interface offered by an Agora server consists of a small and simple set of primitives (see Table 1), which trigger specific processing requests over tuple space content.

**Table 1. Primitive Set of Agora**

Primitives	Timeout <sup>a</sup>	Request Description
<b>Post</b>	Yes <sup>b</sup>	Add a tuple to a tuple space
<b>Pick</b>	Yes <sup>c</sup>	Extract a tuple from a tuple space
<b>Peek</b>	Yes <sup>c</sup>	Read a tuple in a tuple space
<b>Cancel</b>	No	Terminate a pending pick/peek request

a. optional temporal constraint (specified as an optional parameter of the primitive)

b. constraint affects tuple persistency

c. constraint affects request persistency

The *post* and *cancel* primitives return control to the caller immediately. The *pick* and *peek* primitives however remain pending at the server until an entry in the tuple space satisfies the tuple template specified by the primitive, an associated temporal constraint takes effect, or a cancel primitive specifying a matching tuple template is issued by another client. It should be noted that the effect of a cancel primitive is not persistent (i.e. it is not withheld by a server if no matching pick/peek request exist when it is processed).

An example message exchange using tuples illustrates how communication is effected using the MicMac Agora:

1) caller Alice sends a message ("Hello") to callee Bob by performing a **post** operation:

**post** Tuple{("sender", "Alice"), ("receiver", "Bob"), ("content", "Hello")} (Tp 1)

2) in order to receive the message, callee Bob must register himself to the tuple space by launching a **pick** request of the same format as shown below:

**pick** Tuple{("sender", "Alice"), ("receiver", "Bob"), ("content", any)} (Tp 2) or

**pick** Tuple{("sender", any), ("receiver", "Bob"), ("content", any)} (Tp 3)

In this example, "sender", "receiver" and "content" are the **keys** of each Tuple, while "Alice", "Bob", "Hello" are the corresponding **values**. These **values** could be Tuples



as well. There is another important reserved variable called **any**, which can be used as the **value** of any **key** to ignore that particular attribute field. In this case, Tp 2 can extract any message from Alice to Bob, while Tp 3 can extract any message from anyone to Bob, etc. provided that all the messages use the same "sender --- receiver --- content" format. Consequently, both the caller and the callee must agree on a certain type of format (key combination) before they communicate. However, if some other agent has knowledge of this format, it could be able to remove or browse all the messages of this type posted on the Tuple space, thereby giving rise to several security problems. These problems include, but are not limited to message reply, modification of information, passive eavesdropping, denial of services etc.

Ensuring secure communication on top of the MicMac tuple space is essential to the entire system integrity of PMMS. As indicated above, the security strength of MicMac Agora depends on the confidentiality of the tuple format (i.e. the randomness of the keys that constitute the tuple attributes). The API of the MicMac Agora as used in PMMS does not permit an agent to pick/peek messages on the tuple space unless it has the knowledge of the key combination. Both the calling agent and the called agent must agree on a certain pattern for their communication session in order to proceed. Specifically, according to the PMMS, both agents employ a "sender --- receiver --- content" tuple format to exchange messages.

There are several security risks in this system. Firstly, in order to establish a secure communication session, all parties involved in the communication should secretly agree on a key combination prior to exchanging messages. In addition to adding significant processing overhead, this scheme is vulnerable to attackers, as set forth in greater detail below. Secondly, the key combination must be changed frequently. Otherwise, a compromised combination gives rise to compromised future communications using this key combination. More importantly, if a malicious agent is permitted access to the physical memory on the server which supports the MicMac Agora, the agent will be able to eavesdrop on, or arbitrarily modify any tuple.

Another example will serve to illustrate the possible consequences of a compromised key combination (namely, messages exchanged on top of MicMac

being recorded, replayed, modified or removed by some entity other than the expected receiver). Assume that the format of the tuple in a communication session between Alice and Bob is "sender --- receiver --- content", and an attacker happens to know this format. The attacker can then issue any of the attacks listed in Table 2, for malicious purposes.

**Table 2. Attacks on MicMac Tuple**

Attack	Action
Record/Eavesdropping	<b>Peek Tuple</b> {("sender", any), ("receiver", any), ("content", any)}
Remove/Denial of Service	<b>Pick Tuple</b> {("sender", any), ("receiver", any), ("content", any)}
Bomb/Denial of Service	<b>Post Tuple</b> {("sender", "Alice"), ("receiver", "Bob"), ("content", "It's party time!")}
Message Replay	<b>Peek</b> , then <b>post</b> the original Tuple in a later time
Message Reorder	<b>Pick all</b> , then <b>post</b> those messages in a different order
Modify/Active Wiretapping	<b>Pick</b> , change the <i>values</i> , then <b>post</b> the modified version

In order to launch any of the above requests, the attacker requires knowledge of the tuple format between Alice and Bob. However, experience has shown that software hackers are adept at obtaining such information. In fact, this information may become available to the attacker as a result of the negotiation which must take place between Alice and Bob before they exchange the actual messages, in order to decide on the tuple format. Of course, either party (Alice or Bob) can send secure e-mail or certified mail to the other party concerning the format of their next communication. However, human intervention is required in order to change the program periodically to introduce different tuple formats. On the other hand, use of a default pattern such as "sender --- receiver --- content", although automatic, allows an attacker to peek the contents of the messages exchanged between Alice and Bob in order to determine the tuple format and launch attacks later on.

Based on the concept of a Virtual Private Network (VPN), an information fortress model has been developed in accordance with the invention for the communication framework of the system. As illustrated in Figure 2, Coordinators in each site act as "software routers" forming a "virtual firewall" for separating incoming and outgoing messages from the intra-site communications. Two types of tuple spaces are employed to handle inter-agent communications. All of the outgoing messages are

encrypted and then posted to a Shared Tuple Space which is known to all sites/organizations in the network, whereas the intra-site communication messages are exchanged on a Private Tuple Space known only to local agents. These latter messages may either be encrypted or exchanged in clear form. If encrypted, the local encryption keys are completely irrelevant to the Coordinators.

The framework of Figure 2 allows the system to ensure secure communication between sites, independently of the agents. Since it is the responsibility of the Coordinators to implement inter-site data encryption, decryption and other security operations such as digital signature, agents can be developed and implemented without requiring consideration of inter-site communication privacy. Provided that the Coordinators are properly installed and configured at each site, the architecture of a system in accordance with the inventive framework may be implemented on a very large scale.

The Coordinator Manager (CM) is a software component which is responsible for initializing and managing the site Coordinators. There is only one CM at each site. The identity/name of the site CM is the only public information provided to the outside world, and it is globally unique. One pair of Coordinators is created/initiated for every inter-site communication session by the CMs of the two sites, following successful user/agent authentication. This framework also enables the Coordinators to screen the sender's information, such as the caller's ID, for each outgoing message. This feature is particular important in countering *Traffic Analysis* attacks which might otherwise be launched against the MicMac Tuple Space.

To illustrate how the framework of Figure 2 works, consider an example wherein Alice from Mitel sends a "Hello" message to Bob at NRC . Figure 3 shows the message flow for such an exchange. According to the framework, Alice first posts a tuple to the *Private Tuple Space* at Mitel:

(1)  $Tuple\{("sender", "Alice@Mitel"), ("receiver", "C01@Mitel"), ("forwardTo", "Bob@NRC"), ("content", "Hello")\}$

The coordinator "C01@Mitel" then picks this tuple by listening to the Private Tuple Space, as follows:

(2)  $Tuple\{("sender", any), ("receiver", "C01@Mitel"), ("forwardTo", any), ("content", any)\}$

Then, the coordinator will convert the picked tuple to another tuple, and post it to the *Shared Tuple Space*:

5 (3)  $Tuple\{("sender", "C01@Mitel"), ("receiver", "C02@NRC"), ("content", aTuple)\}$

Where  $aTuple = Tuple\{("sender", "Alice@Mitel"), ("receiver", "Bob@NRC"), ("content", "Hello")\}$

Next, the coordinator called "C02@NRC" picks this tuple by registering the  
10 following request at the Shared Tuple Space:

(4)  $Tuple\{("sender", "C01@Mitel"), ("receiver", "C02@NRC"), ("content", any)\}$

After stripping off the unwanted headers, C02@NRC forwards the content to Bob via the Private Tuple Space at NRC in form of a tuple, as follows:

15 (5)  $Tuple\{("sender", "C02@NRC"), ("receiver", "Bob@NRC"), ("content", aTuple)\}$

Bob then retrieves the message from the Private Tuple Space by sending a pick request as follows:

(6)  $Tuple\{("sender", "C02@NRC"), ("receiver", "Bob@NRC"), ("content", any)\}$

20

Finally, Bob parses the tuple and extracts the value of *content*, thereby recovering the message "Hello" from Alice.

If both Coordinators have agreed on one secret key, tuples on the *Shared Tuple Space*, such as the tuple (3), can be encrypted (completely or partially) using the secret key, as follows:

Part encryption:

(a)  $Tuple\{("sender", "C01@Mitel"), ("receiver", "C02@NRC"), ("content", E(aTuple))\}$

30

(b)  $\text{Tuple}\{(E(\text{"sender"}), \text{"C01@Mitel"}), (E(\text{"receiver"}), \text{"C02@NRC"}),$   
 $(E(\text{"content"}), a\text{Tuple})\}$

Full encryption:

5 (c)  $\text{Tuple}\{(E(\text{"sender"}), E(\text{"C01@Mitel"})), (E(\text{"receiver"}), E(\text{"C02@NRC"})),$   
 $(E(\text{"content"}), E(a\text{Tuple}))\}$

wherein  $E(\text{"string"})$  means encrypt the string ("string"), which can be a key or a  
 value, and wherein  $E(a\text{Tuple})$  means encrypt all of the keys and values of the tuple  
 10 (aTuple).

The first expression (a) only encrypts the value of the content field, so that an  
 attacker would still be able to remove this tuple or use the same format to send  
 "spam" messages to Bob. By way of contrast, the expression (c), although offering  
 15 full security, is unwieldy and time consuming to implement. From a security point of  
 view, the full encryption of (c) offers no advantages over (b) provided that appropriate  
 measures are taken to protect the physical memory of the MicMac server from being  
 scanned by unauthorized agents.

20 Nonetheless, the full encryption provided by (c) enables an agent to hide  
 sensitive information inside the content of the embedded tuple so that neither the  
 Coordinators nor other unintended agents are able to browse it. Moreover, the  
 Coordinators of the session can utilize the outer fields of the message to include  
 information for other network services such as routing or QoS. This control  
 25 information is encrypted in order to counter *Traffic Analysis* attacks. Furthermore, it is  
 important that this information not be encrypted using the same key as the one for the  
 embedded tuple since the Coordinator would then be able to perform decryption on  
 the embedded tuple and see the original message. Accordingly, two different session  
 keys must be used, one ( the outer key) for control information, and another (the inner  
 30 key) for the embedded tuple (i.e. the "real" data). Rather than using two protocols for  
 generating the inner and outer keys, any one of several well known traditional and  
 reliable protocols may be used to establish the inner key, while the outer key is  
 computed out of the inner key using a one way hash function. One advantage of this

solution is that the Coordinators can only encrypt/decrypt the control information, whereas the end users (i.e. caller and callee) are able to encrypt/decrypt the entire tuple.

5           Returning to the previous example, and assuming that the inner and outer keys have been created, the following message exchange takes place, wherein  $E_o("M")$  means encrypt string M using the outer key, and  $E_i("M")$  means encrypt M with the inner key.

10           First, Alice **posts** the following encrypted tuple to the Private Tuple Space.

(1)  $Tuple\{(E_o("sender"), E_o("Alice@Mitel")), (E_o("receiver"), E_o("C01@Mitel")), (E_o("forwardTo"), E_o("Bob@NRC")), (E_o("content"), E_i("Hello"))\}$

15           The Coordinator "C01@Mitel" **picks** this tuple from the Private Tuple Space as follows:

(2)  $Tuple\{(E_o("sender"), any), (E_o("receiver"), "C01@Mitel"), (E_o("forwardTo"), any), (E_o("content"), any))\}$

Then, the Coordinator converts this tuple, and **posts** it to the *Shared Tuple Space*:

20           (3)  $Tuple\{(E_o("sender"), E_o("C01@Mitel")), (E_o("receiver"), E_o("C02@NRC")), (E_o("content"), aTuple)\}$

Where  $aTuple = Tuple\{(E_o("sender"), E_o("Alice@Mitel")), (E_o("receiver"), E_o("Bob@NRC")), (E_o("content"), E_i("Hello"))\}$

25           Next, the Coordinator "C02@NRC" **picks** this tuple by registering the following request on the Shared Tuple Space:

(4)  $Tuple\{(E_o("sender"), E_o("C01@Mitel")), (E_o("receiver"), E_o("C02@NRC")), (E_o("content"), any)\}$

30           After stripping off the unwanted headers, C02@NRC forwards the contents to Bob via the Private Tuple Space at NRC in form of the following tuple:

(5)  $Tuple\{(Eo("sender"), Eo("C02@NRC")), (Eo("receiver"), Eo("Bob@NRC")), (Eo("content"), aTuple)\}$

Bob retrieves the message from the Private Tuple Space by sending the following **pick** request:

5 (6)  $Tuple\{(Eo("sender"), Eo("C02@NRC")), (Eo("receiver"), Eo("Bob@NRC")), (Eo("content"), any)\}$

Finally, Bob parses the tuple and extracts the value of *content*, decrypts and then recovers the message "Hello" from Alice.

10 Since one random key needs to be created prior to the establishment of the secure communication session, an authentication framework has been developed in accordance with the present invention for implementing a proper authentication and key exchange protocol.

15 With reference to Figure 4, the caller (e.g. Alice) initiates the request (1) and sends it to the local site CM (e.g. Mitel\_CM) via the Private Tuple Space A. The Mitel\_CM picks the request (2), locates the home site of the intended receiver (e.g. Bob at NRC), and then transmits the request to the NRC site (3). Upon receiving the calling request (4), the NRC\_CM transfers the request to Bob via the Private Tuple  
 20 Space B at NRC ((5) and (6)). Before establishing the connection, the NRC\_CM activates the Authentication Agent (User Logon Agent is an instance of Authentication Agent) to authenticate the caller. The agent proposes an authentication and key exchange protocol back to the Mitel\_CM together (optionally) with some additional parameters via the dotted virtual path in Figure 4. The Mitel\_CM decides  
 25 whether or not to activate the second Authentication Agent, according to the local site security policy. Provided that the proposed authentication and key exchange protocol is allowed and supported at Mitel site, the two Authentication Agents follow the established schema to mutually authenticate the caller and the callee. During this authentication process, both the caller and the callee may be contacted by the  
 30 Authentication Agents, which may or may not verify their identities against the site's private Data Repository (D. R.).

As a result of successful authentication and key exchanges, the two Authentication Agents agree on three pieces of secret information: one session key and two dynamic identifiers. The session key (i.e. inner key) is passed to the caller (Alice) and the callee (Bob), whereas the hashed value of the session key and the two identifiers are used to generate Coordinator instances. The creation of the two Coordinators establishes the secure communication session between Alice and Bob. The hashed value (i.e. outer key) assigned to the Coordinators is used to encrypt/decrypt all of the keys of the tuples as well as the values of outer fields used for control purpose. Alice and Bob then use the inner key to encrypt/decrypt the embedded tuple.

In accordance with another aspect of the invention, each site CM maintains a dynamic table containing the Ids of all on-line (i.e. active) agents and the Ids of their corresponding Coordinators. Using this table, the site CM is able to detect possible *Impersonation* attacks. By defining a unique ID for each agent, it is easy for the system to make sure that at any given time, there is no more than one session established for a particular agent.

Without a positive result of the authentication procedure, a communication session will not be initialized since no Coordinator will have been created. Thus, the only possible way for an attacker to break an established session is to correctly guess the two random IDs (preferably 64 bits each) of the Coordinators and the session key (preferably 112 bits). Such a correct guess would be extremely difficult and computationally infeasible.

Integrity checking is another important technique employed in the present invention to ensure secure communication. To achieve this, a Digital Signature is attached to the original message. Integrity of a message can then be verified by performing the same signature function on the message and comparing the result with the attached Digital Signature. In symmetric cryptosystem, digital signatures can be computed using one way hash functions such as MD4, MD5 or SHA (Secure Hash Algorithm). The a successful prototype of the present invention supports all of the foregoing signature functions.



The format for the tuples used in inter-site communication preferably should conform to a predetermined format, as shown in Figure 5.

5       The *Message ID* specifies a unique sequence number as well as the type of the message. *Security Header* contains information about the security settings of the current communication session, including the names of the encryption algorithm, the signature function and some parameters. An example of a security header is "Triple\_DES-112 SHA-80". *Sender ID* and *Receiver ID* specify the expected sender  
10       and receiver of the tuple (which can, for example, be the names of the site CMs during the initialization period or the dynamic IDs of the Coordinators constituting the secure session). *Forward To* is used when one agent sends a message to another agent at a different site via Coordinators. The *Signature* field contains the digital signature of the entire tuple. The *Content* field is used to carry real communication data or the  
15       embedded tuple. For additional control information, the *Others* field can be used. Moreover, additional *Others* fields may be added if needed.

During the initialization phase (i.e. authentication and key exchange), attributes are not encrypted. Furthermore, some attributes may not be used such as  
20       *Security Header*, *Others* and *Signature*. However, once a secure session has been established, all of the attributes are used and encrypted.

Figure 6 illustrates the entire process for establishment of a secure communication session between Alice and Bob, including the message exchanges  
25       between them. In this example, it is assumed that both waiting time and response time for all the exchanged tuples are negligible. This means that a posted tuple will be removed from the tuple space immediately, which indicates that the corresponding pick request should be registered at the tuple space prior to the arrival of the posted tuple. Continuing on the basis of this assumption, there are six pre-registered pick  
30       requests for all of the three tuple spaces, with the format of the inter-site tuples being as set forth in Figure 5, and the format for the intra-site tuples being the same (for the sake of simplicity):

any	basic	CM@Mitel	Alice@Mitel	null	any	any	any
-----	-------	----------	-------------	------	-----	-----	-----

1.

2.	any	basic	any	CM@Mitel	any	any	any	any
----	-----	-------	-----	----------	-----	-----	-----	-----

5

3.	any	basic	any	CM@Mitel	null	any	any	any
----	-----	-------	-----	----------	------	-----	-----	-----

4.	any	basic	any	CM@NRC	null	any	any	any
----	-----	-------	-----	--------	------	-----	-----	-----

10

5.	any	basic	any	CM@NRC	any	any	any	any
----	-----	-------	-----	--------	-----	-----	-----	-----

6.	any	basic	CM@NRC	Bob@NRC	null	any	any	any
----	-----	-------	--------	---------	------	-----	-----	-----

The first tuple, for example, would be:

15 *Tuple*{("Message ID", any), ("Security Header", "basic"), ("Sender ID", "CM@Mitel"), ("Receiver ID", "Alice@Mitel"), ("Forward To", null), ("Others", any), ("Signature", any), ("content", any)}

The value "basic" can be defined as "null-0-sha-80", which means the tuple is not encrypted but is digitally signed using Secure Hash Algorithm. The signature  
20 contained in the tuple is the first 80 bits of the SHA output/digest.

Moreover, in order to carry binary data in a tuple, this data must be converted into a text stream. Base64 Encoding, as defined in MIME, was employed as the only one encoding algorithm in the successful prototype of this invention.

25

Tuples (1) through (3) are the initial tuples requesting the authentication process between Alice and Bob, as follows:

(1)	0001	basic	Alice@Mitel	CM@Mitel	Bob@NRC	null	sig1	Hello
-----	------	-------	-------------	----------	---------	------	------	-------

30 where sig1 stands for the actual encoded signature stream of the tuple,

(2)	0002	basic	CM@Mitel	CM@NRC	Bob@NRC	null	sig2	Tuple 1
-----	------	-------	----------	--------	---------	------	------	---------

where **sig2** is the signature of the tuple, and **Tuple 1** is an embedded tuple defined as:  
*Tuple*{("Message ID", "0001"), ("Sender ID", "Alice@Mitel"), ("Receiver ID",  
 "Bob@NRC"), ("content", "Hello")}

5	(3)	0003	basic	CM@NRC	Bob@NRC	null	null	sig3	Tuple 1
---	-----	------	-------	--------	---------	------	------	------	---------

where **sig3** is the signature for tuple (3), and **Tuple 1** is the same one as described above in tuple (2).

10 Before posting any tuple to the tuple space, the creator/sender of the tuple is responsible for calculating the digital signature for the entire tuple. On the other hand, the receiver must verify the integrity of the tuple by checking the value of the signature field immediately after removing a tuple from the tuple space. If the receiver determines that the tuple has been changed during transmission, the receiver discards  
 15 the message and/or asks the sender to re-send it.

Once Bob recovers the "Hello" message, the mutual authentication process begins. The authentication agent inside the site CM (see Figure 4) is responsible for initiating this task. The details of the authentication process are not described in any  
 20 further detail herein, but conform to well known standard authentication and key exchange protocols.

As a result of the authentication and key exchange process, the two parties have an agreed security setting (SecSet) for the session, and the following random  
 25 numbers have been generated:

- a. An **inner key (Ki)**, which is the result of the key exchange.
- b. Two dynamic IDs (**RM** and **RN**), which are used to create dynamic Coordinators for the session.
- c. An **outer key (Ko)**, which is the hashed value of the **inner key**.

30

**Ki** is passed to Alice and Bob by their respective corresponding authentication agents. **RM**, **RN** and **Ko** are used as parameters when creating the Coordinator

instances: **RM** as the identifier for the Mitel Coordinator and **RN** for the NRC Coordinator.

After establishment of the communication session, Alice, Bob and the two Coordinators immediately register to the tuple spaces for any incoming messages. Figure 6 shows registration of six (7 ~ 12) such requests, in total, wherein the keys/attributes of the tuple are encrypted using **Ko**:

7.

any	SecSet	RM@Mitel	Alice@Mitel	null	any	any	any
-----	--------	----------	-------------	------	-----	-----	-----

The text version for the above tuple is:

*Tuple{(Eo("Message ID"), any), (Eo("Security Header"), "SecSet"), (Eo("Sender ID"), "RM@Mitel"), (Eo("Receiver ID"), "Alice@Mitel"), (Eo("Forward To"), null), (Eo("Others"), any), (Eo("Signature"), any), (Eo("content"), any)}*

8.

any	SecSet	Alice@Mitel	RM@Mitel	Bob@NRC	any	any	any
-----	--------	-------------	----------	---------	-----	-----	-----

The value of the field "Forward To" (Bob@NRC) is optional, because RM@Mitel will only communicate with RN@NRC, which forwards the message to Bob only.

9.

any	SecSet	RN@NRC	RM@Mitel	Alice@Mitel	any	any	any
-----	--------	--------	----------	-------------	-----	-----	-----

10.

any	SecSet	RM@Mitel	RN@NRC	Bob@NRC	any	any	any
-----	--------	----------	--------	---------	-----	-----	-----

11.

any	SecSet	Bob@NRC	RN@NRC	Alice@Mitel	any	any	any
-----	--------	---------	--------	-------------	-----	-----	-----

12.

any	SecSet	RN@NRC	Bob@NRC	null	any	any	any
-----	--------	--------	---------	------	-----	-----	-----

Because of the randomness of the outer key (**Ko**), which is used to encrypt the attributes, it is infeasible for any other agent to generate any of the above requests.

After the foregoing message exchange, Alice sends her message to Bob in a secret way. First, she encrypts the message (**Msg**) using the inner key (**Ki**), and assigns the result of the encryption (**Ei(Msg)**) as the value of the content, or more accurately, the **Eo("content"))** field.

5      (4)

0004	SecSet	Alice@Mitel	RM@Mitel	Bob@NRC	null	sig4	Ei(Msg)
------	--------	-------------	----------	---------	------	------	---------

This tuple is then picked by **RM@Mitel**, and forwarded to **RN@NRC** in the following tuple:

10      (5)

0005	SecSet	RM@Mitel	RN@NRC	Bob@NRC	null	sig5	Ei(Msg)
------	--------	----------	--------	---------	------	------	---------

It should be noted that, in tuple (5), although an embedded tuple could be used in the content field, it is not necessary since Bob will know that the message comes from Alice once he receives the following one from **RN@NRC**.

15

0006	SecSet	RN@NRC	Bob@NRC	null	null	sig6	Ei(Msg)
------	--------	--------	---------	------	------	------	---------

After Bob receives this tuple, he can decrypt the value of the content field (**Ei(Msg)**) using the inner key (**Ki**) and thereby recover the message **Msg** from Alice.

20

In summary, according to the present invention the hashed value of the random inner key which is used to encrypt pure communication data or embedded tuples, is used to encrypt the header information for control purpose. Therefore, communication entities/agents are able to see the entire content of a tuple, whereas  
 25 authorized routing components or Coordinators only see the format of the tuple and some control information. Unauthorized agents or Coordinators are prevented from seeing any tuple content of an established session even if they have knowledge of the format/key combinations of the session.

30

Other embodiments and variations of the invention are possible. All such additional embodiments and applications are believed to be within the sphere and scope of the invention as defined by the claims appended hereto.

What is claimed is:

1. A virtual network communication system for effecting secure communications between user agents at different sites within said virtual network, comprising:

5

at least one Private Tuple Space within each of said sites for effecting intra-site communications between agents at each of said sites;

10 a Shared Tuple Space for effecting inter-site communications between said different sites; and

15 a Coordinator Manager within each of said sites for receiving user initiated communication requests from said Private Tuple Space to communicate between user agents at said different sites, authenticating said requests and in response dynamically creating and managing instances of Coordinators at each of said different sites which embed messages from said user agents in secure tuples and exchange said secure tuples over said Shared Tuple Space.

20 2. The virtual network communication system of claim 1, wherein each said Coordination Manager further includes an Authentication Agent for negotiating authentication and key exchange protocols there between and in response generating and forwarding an inner key to each of said user agents at said different sites for encrypting and decrypting said messages embedded in said secure tuples, and for generating two dynamic identifiers used to create said Coordinator instances and a  
25 hashed value of said inner key for encrypting and decrypting said secure tuples.

3. The virtual network communication system of claim 2, further including a Data Repository within each of said sites for storing authentication data applicable to local ones of said user agents, said authentication data being accessible to said  
30 Authentication Agent for negotiating said authentication and key exchange protocols.

4. The virtual network communication system of claim 1, wherein said Coordinator Manager further includes a dynamic table containing IDs of all active

ones of said user agents and corresponding ones of said Coordinators for detection of impersonation attacks against said virtual network communication system.

5        5.        The virtual network communication system of claim 1, wherein said Coordinators calculate and verify digital signatures for each of said secure tuples thereby ensuring message integrity.

6.        A method of effecting secure virtual network communications between user agents at different sites within said virtual network, comprising the steps of:

10                authenticating user initiated requests to communicate between user agents at said different sites;

15                generating and forwarding an inner key to each of said user agents at said different sites for encrypting and decrypting messages exchanged there between; and

              dynamically creating and managing instances of Coordinators at each of said different sites for embedding said messages in secure tuples and exchanging said secure tuples over a Shared Tuple Space between said different sites.

20

7.        The method of claim 6, further comprising the steps of generating two dynamic identifiers for creating said Coordinator instances and generating a hashed value of said inner key as said outer key for encrypting and decrypting said control information in said secure tuples.

25

8.        The method of claim 6, further comprising the step of separating QoS and other control information needed by said network from user information communicated between said user agents.

30        9.        The method of claim 8, further comprising the steps of:

encrypting and decrypting said user information in embedded tuples exchanged on Shared Tuple Space by each of said user agents at said different sites using said inner key; and

- 5        encrypting and decrypting said secure tuples and control information exchanged on said Shared Tuple Space by said Coordinator instances using a hash value of said inner key for effecting secure dynamic sessions.



## ABSTRACT

According to the present invention, a virtual network communication system is provided for effecting secure communications between user agents at different sites within said virtual network, comprising at least one Private Tuple Space within each of the sites for effecting intra-site communications between the agents, a Shared Tuple Space for effecting inter-site communications between different sites, and a Coordinator Manager within each of the sites for receiving user initiated communication requests from the Private Tuple Space to communicate between user agents at the different sites, authenticating the requests and in response dynamically creating and managing instances of Coordinators at each of the different sites which embed messages from the user agents in secure tuples using multi-layered encryption and exchange the secure tuples over the Shared Tuple Space.

**THIS PAGE BLANK (USPTO)**




Figure 1A

**THIS PAGE BLANK (USPTO)**






Figure 1B

**THIS PAGE BLANK (USPTO)**

**Figure 2**

**THIS PAGE BLANK (USPTO)**



**Figure 3**

**THIS PAGE BLANK (USPTO)**




Figure 4




Figure 5

**THIS PAGE BLANK (USPTO)**




Figure 6

**THIS PAGE BLANK (USPTO)**